


MAXIMUM 1760 KW (2360 HP) @ 1800 RPM [CONTINUOUS DUTY]**STANDARD EQUIPMENT****MG-5600 DR**

12V or 24V electric selector valve
 Companion flange/bolt set
 Oil pressure/oil temperature gauges
 Oil strainer and oil filter
 Raw/fresh water heat exchangers

**OPTIONS**

ABS certificates and other survey societies certificates – consult Twin Disc, Inc. for details
 Companions flange for shaft brake (disc type)
 Electric trailing oil pump
 Flexible/torsional input couplings
 Heat exchanger with thermostat
 Live PTO for customer-supplied hydraulic pump
 Size 127-2/-4, 32-4 (SAE 2/4 bolt-'C')
 PTO torque rating = 592 N-m (437 lb-ft)
 PTO turns opposite to engine direction and not at engine speed, depending on input ratio
 Metric to NPTF adapter kit
 Mounting brackets
 Oil pump(s) to accommodate LH rotation engine
 Weight (dry weight with standard equipment)

MG-5600 DR**X****X****X****X****X****X****X****X****X****X****X****X****3465 kg**

Contact Twin Disc for Survey Society Approvals and Classifications.

Specifications subject to change without prior notice in the interest of continual product improvement.

INPUT RATINGS – KILOWATTS (KW) (HORSEPOWER [HP])*

MG-5600 DR	Reduction Ratios :1	Continuous Duty			Max rated input speed and min. engine low idle speed RPM
		@ 1200 RPM	@ 1600 RPM	@ 1800 RPM	
	6.02	1151 kW (1543hp)	1574 kW (2097 hp)	1760 kW (2360 hp)	475 min. 2100 max.
	6.56	1038 kW (1392 hp)	1458 kW (1955 hp)	1641 kW (2200 hp)	
	7.01	964 kW (1293 hp)	1352 kW (1813 hp)	1566 kW (2100 hp)	

* Ratings shown for use with standard right hand rotation engines.

SERVICE CLASSIFICATION DEFINITIONS

Pleasure Craft [PC]: Up to 500 hours/year, low load factor usage planing hull vessels where typical full engine throttle operation is less than 10% of total time. The balance of operation at 80% of full engine throttle or less. Marine transmissions for use in long range pleasure cruisers, sportfish charter boats/patrol boats do not qualify for Pleasure Craft Service.

Note: Some revenue producing applications such as Planing Hull Bristol Bay Gillnetter do qualify under Pleasure Craft rating definition.

Light Duty [LD]: Relatively low hour usage (less than 1500 hours per year) where full throttle operation is 2 hours out of 12. Typical applications include planing hull vessels such as fire boats, sportfish charter boats, and patrol/custom boats. This rating is also applicable to some bow and stern thruster applications.

Intermediate Duty [ID]: Hour usage of up to 2000 hours/year (for models MG-5114 Series and smaller) and up to 3000 hours/year (for models larger than MG-5114 Series) with 50% of the operating time at full engine rating. Typical applications include planing hull vessels such as ferries, fishing boats, some crew boats, and some displacement hull yachts as well as some bow and stern thruster applications.

Medium Duty [MD]: Hour usage of up to 4000 hours/year with up to 80% of operating time at full engine power. This duty classification is for usage where some variations in engine speed/power occur as part of normal vessel operation. Typical vessels include mid-water trawlers, crew/supply boats, ferries, and some inland water tow boats.

Continuous Duty [CD]: For use in continuous operation with little or no variation in engine speed/power setting. Typical vessels include fishing trawlers, tow/tug boats and ocean going vessels.

Important Notice: Torsional Vibration: Disregarding propulsion system torsional compatibility could cause damage to components in the drive train resulting in loss of mobility. At minimum, system incompatibility could result in gear clatter at low speeds.

The responsibility for ensuring that the torsional compatibility of the propulsion system is satisfactory rests with the assembler of the drive and driven equipment.

Torsional vibration analysis can be made by the engine builder, marine survey societies, independent consultants and others. Twin Disc is prepared to assist in finding solutions to potential torsional problems that relate to the marine transmission.

Twin Disc, Incorporated reminds users of these products that their safe operation depends on use in compliance with engineering information provided in this bulletin. Users are also reminded that safe operation depends on proper installation, operation and routine maintenance and inspection under prevailing conditions. It is the responsibility of the user (and not Twin Disc, Incorporated) to provide and install guards or safety devices which may be required by recognized safety standards or by the Occupational Safety and Health Act of 1970 and its subsequent provision.



Twin Disc, Incorporated
Racine, Wisconsin 53403 U.S.A
Phone +1-262-638-4000
Fax +1-262-638-4482
www.twindisc.com